



## Product certificate K99067/01

Issued 2018-07-01

Replaces n/a

Page 1 of 2

### Sanitary tapware: Mechanical mixers

#### STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

### Ideal-Standard Produktions-GmbH

as specified in this product certificate and marked with the Kiwa<sup>®</sup>-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K607/04 "Sanitary tapware: Mechanical mixers" d.d. 01-02-2012.

Luc Leroy  
Kiwa

288171015

*Publication of this certificate is allowed.*

*Advice: consult [www.kiwa.nl](http://www.kiwa.nl) in order to ensure that this certificate is still valid.*

#### Kiwa Nederland B.V.

Sir Winston Churchilllaan 273  
P.O. Box 70  
2280 AB RIJSWIJK  
The Netherlands  
Tel. +31 88 998 44 00  
Fax +31 88 998 44 20  
[info@kiwa.nl](mailto:info@kiwa.nl)  
[www.kiwa.nl](http://www.kiwa.nl)

#### Company

Ideal-Standard Produktions-GmbH  
Röntgenstrasse 9  
54516 Wittlich, Germany  
Tel. +49 6571 160  
Fax +49 6571 16 9276  
[info@idealstandard.com](mailto:info@idealstandard.com)  
[www.idealstandardinternational.com](http://www.idealstandardinternational.com)

Certification process  
consists of initial and  
regular assessment of:

- quality system
- product

## Sanitary tapware: Mechanical mixers

---

### PRODUCT SPECIFICATION

The products mentioned below belong to this certificate.

#### SERIES CERAFLEX

F1756AA	Basin mixer
F1757AA	Basin mixer
F1758AA	Basin mixer
F1759AA	Basin mixer
F1760AA	Basin mixer
F1761AA	Basin mixer
F1763AA	Bath Shower mixer

#### SERIES CONNECT AIR

F1751AA	Basin mixer
---------	-------------

### APPLICATION AND USE

The mechanical mixers are designed for application within following limits of use:

- working pressure from 50 kPa up to 1000 kPa;
- water temperature of maximum 90°C.

The recommended limits for correct operation are:

- working pressure of 100 kPa up to 500 kPa;
- water temperature of maximum 65°C.

### MARKING

The Kiwa®-mark products are marked with the wordmark "KIWA".

Place of the mark:

- on the body.

Compulsory specifications:

- name or mark of the manufacturer: "BORMA" on the body;
- indication of the acoustic group, if classified: on the body;
- indication of the flow rate class: on the body.

Method of marking:

- non-erasable;
- visible after assembly.

### RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Ideal-Standard Produktions-GmbH  
and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.